

The perfect promotion platform.

# M425



Verifone's newest member of multilane devices, the M425 is flexible enough to support many use cases - indoor attended, integrated or semi-integrated, WiFi, Ethernet, or USB. The vibrant display is perfect for promoting your brand, showcasing seasonal promotions, encouraging loyalty, and even training team members. Expand your eCommerce capabilities by accepting Advanced Payment Methods like PayPal or Klarna, providing your customers the convenience of buy online return in store, and more. Backward compatible and forward thinking, the M425 utilizes the same cabling and mounting stands as our M440 and M424 devices making field replacements smooth while saving you valuable time and money.

- Perfect for integrated or semi-integrated use cases
- Three SAM slots to support multiple bank payment
- Android or Engage OS
- Cables and stands are backward compatible with M440 and M424 cabling/stands
- Add powerful eCommerce solutions with Verifone Cloud Services including APMs, Device Management, Gateways and more.

<b>Display</b>	5.5" Color LCD   Capacitive Multi-touch   LED Backlit Display   Resolution 720 x 1280 HD
<b>Multimedia</b>	Audio Jack   Buzzer   Microphone   Speaker   Video & Audio Playback
<b>User Interface</b>	Backlit Keypad   Tactile 15 Key Keypad
<b>Camera   Barcode Scanner</b>	Barcode + OCR + QR Decode   Front 5 MP Fixed Focus
<b>Card Reader</b>	Magstripe ISO 7810, 7811, 7813   Smart Card EMVCo Approved
<b>Contactless</b>	EMVCo Approved   MiFare   Supports Advanced Payment Methods   Supports Major NFC/Contactless Schemes
<b>Connectivity</b>	Bluetooth® v4.2   WiFi 2.4GHz + 5GHz 802.11 a/b/g/n/ac
<b>Memory</b>	2GB RAM + 16GB Flash

<b>Operating System</b>	Verifone Secure OS, Engage VOS3 AVOS Based on Android 10
<b>Processor</b>	ARM Cortex A53, Quad Core, 1.3 GHz
<b>Security</b>	PCI PTS 6.x Approved
<b>Connections</b>	LAN 10/100 Base-T   RS232   USB RJ45 for Host/Device   USB Type-C
<b>Power</b>	Rating 12V, 1.5A, DC Jack
<b>Physical</b>	179mm L x 170mm W x 29mm H   Weight 470g
<b>Environmental</b>	IK Rating IK04   IP Rating IP53   Operating Temperature: -10° to 50° C (14° to 122° F)   Storage Temperature: -20° to 60° C (-4° to 140° F)   Relative Humidity 5% to 90%, Non-condensing
<b>Other Standard Features</b>	Card Slots 3 SAM   Anti-Theft Slot
<b>Accessories</b>	Mounting Plate   Mounting Pole   Privacy Shield   Stylus

