MULTILANE | M425 GEN 2 PLUS

The perfect promotion platform.

M425

Verifone's newest member of multilane devices, the M425 is flexible enough to support many use cases - indoor attended, integrated or semi-integrated, WiFi, Ethernet, or USB. The vibrant display is perfect for promoting your brand, showcasing seasonal promotions, encouraging loyalty, and even training team members. Expand your eCommerce capabilities by accepting Advanced Payment Methods like PayPal or Klarna, providing your customers the convenience of buy online return in store, and more. Backward compatible and forward thinking, the M425 utilizes the same cabling and mounting stands as our M440 and M424 devices making field replacements smooth while saving you valuable time and money.

- Perfect for integrated or semi-integrated use cases
- Three SAM slots to support multiple bank payment
- Android or Engage OS

- Cables and stands are backward compatible with M440 and M424 cabling/stands
- Add powerful eCommerce solutions with Verifone Cloud Services including APMs, Device Management. Gateways and more.

Display	5.5" Color LCD | Capacitive Multi-touch | LED Backlit Display | Resolution 720 x 1280 HD
Multimedia	Audio Jack | Buzzer | Microphone | Speaker | Video & Audio Playback
User Interface	Backlit Keypad | Backlit contactless Icon | Tactile 15 Key Keypad | Volume Buttons
Camera | Barcode Scanner	Barcode + OCR + QR Decode | Bottom 2 MP Fixed Focus with Red Aimer | Front 5 MP Auto Focus
Card Reader	Magstripe ISO 7810, 7811, 7813 | Smart Card EMVCo Approved
Contactless	EMVCo Approved | MiFare | Supports Advanced Payment Methods | Supports Major NFC/Contactless Schemes
Connectivity	Bluetooth® v5.0 | WiFi 2.4GHz + 5GHz 802.11 a/b/g/n/ac
Memory	2GB RAM + 32GB Flash | Micro SD

Operating System	Verifone Secure OS, Engage VOS3 | VAOS Based on Android 13
Processor	ARM Cortex A53, Quad Core, 2.0 GHz
Security	PCI PTS 6.x Approved | Remote Skimmer Detection
Connections	LAN 10/100 Base-T | RS232 | USB RJ45 for Host/Device | USB Type-C
Power	Rating 12V, 1.5A, DC Jack
Physical	179mm L x 170mm W x 29mm H | Weight 474g
Environmental	IK Rating IK04 | IP Rating IP53 | Operating Temperature: -10° to 50° C (14° to 122° F) | Storage Temperature: -20º to 60º C (-4º to 140º F) | Relative Humidity 5% to 90%, Non-condensing
Other Standard Features	Card Slots 3 SAM | Anti-Theft Slot
Accessories	Mounting Plate | Mounting Pole | Privacy Shield | Stylus

verifone