

PORTABLE | V240M

BUILT FOR INTERACTION  
AND PORTABILITY.

# V240M



The Verifone V240m, part of the Verifone Engage portfolio, combines the latest features, functionality, and performance into one efficient, cost-effective solution. Boasting a large 3.5" color touch display, large memory, a faster processor, and multiple connectivity options, this full-function portable payment device makes doing business on-the-go easy and is ideal for pay-at-the-table, curbside delivery, kiosks and line-busting. Whether you are looking to accept basic payment transactions or explore more advanced capabilities like paying with points, digital couponing and other value-added services, the V240m makes it possible.

- Accepts contactless payments including mobile wallets and NFC enabled cards
- Sleek, modern design with intuitive customer guidance by LEDs and illuminated contactless logo with dual tone buzzer
- Select the V240m with camera to scan QR codes, coupons and accept Advanced Payment Methods
- Designed to easily integrate into existing environments and compatible with many POS host protocols
- Weatherproof enclosure provides top level protection against dust, liquids and other harmful substances
- Tamper resistant and anti vandalism enclosure

<b>Display</b>	3.5" Color LCD   Capacitive Mutli-touch Screen   LED Backlight   Resolution: 320 x 480 HVGA
<b>Multimedia</b>	Speaker
<b>User Interface</b>	Backlit Keypad   Tactile 15 Key Keypad
<b>Camera   Barcode Scanner</b>	Optional Camera
<b>Printer</b>	30 lps   40mm Paper Roll
<b>Card Readers</b>	Magstripe ISO 7810, 7811, 7813   Smart Card EMVCo Approved
<b>Contactless</b>	EMVCo Approved   Supports Major NFC/Contactless Schemes
<b>Connectivity</b>	2G + 3G   Bluetooth® v4.2   WiFi 2.4GHz + 5GHz 802.11 a/b/g/n/ac
<b>Memory</b>	128MB RAM + 256MB Flash Micro SD   Optional 512MB RAM + 512MB Flash

<b>Operating System</b>	Verifone Secure OS, Engage VOS2
<b>Processor</b>	ARM Cortex A9, 600 MHz
<b>Security</b>	PCI PTS 5.x Approved
<b>Connections</b>	Charging + Data Contacts   USB Type-C
<b>Power</b>	Adapter 5VDC, 2.2A   Battery 3.6V, 3350mAh Li-ion   Field Replaceable Battery   Rating 5V, 1A/2.2A, DC Jack
<b>Physical</b>	163mm L x 76mm W x 54mm H   Weight: 315g
<b>Environmental</b>	Operating Temperature: 0° to 50° C (32° to 122° F)   Storage Temperature: -20°to 60° C (-4°to 140° F)   Relative Humidity: 5% to 90%, Non-condensing   Optional ATEX Approved variants
<b>Other Standard Features</b>	Card Slots 2 SIM + 2 SAM
<b>Accessories</b>	Charging base   Full Feature Base   Privacy Shield

